


## Aircraft Cable




1 x 19

Approx. Weight 100 ft (lbs)	Minimum Strength (lbs)	Diameter (in)
0.25	185	1/32
0.55	375	3/64
0.85	500	1/16
1.4	800	5/64
2	1200	3/32
2.7	1600	7/64
3.5	2100	1/8
4.3	2820	9/64
5.5	3300	5/32
7.7	4700	3/16




7 x 7

Approx. Weight 100 ft in lbs	Minimum Strength (lbs)	Diameter (in)
0.36	270	3/64
0.75	480	1/16
1.1	650	5/64
1.6	920	3/32
2.2	1260	7/64
2.8	1700	1/8
4.3	2600	5/32
6.2	3700	3/16
8.3	4800	7/32
10.6	6100	1/4




7 x 19

Approx. Weight 100 ft in lbs	Minimum Strength (lbs)	Diameter (in)
0.25	185	3/32
0.55	375	1/8
0.85	500	5/32
1.4	800	3/16
2	1200	7/32
2.7	1600	1/4
3.5	2100	9/32
4.3	2820	5/16
5.5	3300	3/8



Galv 7x7

Cable Diameter	Coated to	Approx. Wt. per 1000 ft. (lbs)	Breaking Strength (lbs)
1/16"	3/32"	9.3	480
1/16"	1/8"	11.8	480
3/32"	1/8"	18.5	920
3/32"	3/16"	25.8	920
1/8"	3/16"	35.2	1,700



Galv 7x19

Cable Diameter	Coated to	Approx. Wt. per 1000 ft. (lbs)	Breaking Strength (lbs)
3/32"	1/8"	19.9	1,000
1/8"	3/16"	36.2	2,000
3/16"	1/4"	77.5	4,200
3/16"	5/16"	77.5	4,200
1/4"	5/16"	123	7,000
5/16"	3/8"	197	9,800
3/8"	7/16"	270	14,400

SS 7x19

Cable Diameter	Coated to	Approx. Wt. per 1000 ft. (lbs)	Breaking Strength (lbs)
1/8"	3/16"	36.2	1,760
3/16"	1/4"	77.5	3,700
1/4"	5/16"	123	6,400
5/16"	3/8"	197	9,000
3/8"	7/16"	270	12,000